



材料: 钢 45

热处理: 调质HB220-260

NMRV 双向输出轴

规格	dh6	L	L1	L2	E	E1	E2	FXd1	S	B	MX深H
030	$\phi 14_{-0.011}^0$	128	$70_{0}^{+0.10}$	29	20	20	5	$1.1_{0}^{+0.14} \times \phi 13.4_{-0.11}^0$	$11_{-0.10}^0$	$5_{-0.03}^0$	M6-15
040	$\phi 19_{-0.013}^0$	164	$86_{0}^{+0.10}$	39	30	20	6	$1.1_{0}^{+0.14} \times \phi 18_{-0.11}^0$	$15.5_{-0.10}^0$	$6_{-0.03}^0$	M6-15
050	$\phi 25_{-0.013}^0$	199	$101.4_{0}^{+0.10}$	48.8	40	25	10	$1.3_{0}^{+0.14} \times \phi 23.9_{-0.21}^0$	$21_{-0.20}^0$	$8_{-0.036}^0$	M10-16
063	$\phi 25_{-0.013}^0$	219	$121.4_{0}^{+0.10}$	48.8	40	25	10	$1.3_{0}^{+0.14} \times \phi 23.9_{-0.21}^0$	$21_{-0.20}^0$	$8_{-0.036}^0$	M10-16
075	$\phi 35_{-0.013}^0$	249.6	$132_{0}^{+0.10}$	58.8	50	25	8	$1.7_{0}^{+0.14} \times \phi 33_{-0.21}^0$	$30_{-0.20}^0$	$10_{-0.036}^0$	M10-16
090	$\phi 35_{-0.016}^0$	312	$152_{0}^{+0.10}$	80	70	25	10	$1.7_{0}^{+0.14} \times \phi 33_{-0.25}^0$	$30_{-0.20}^0$	$10_{-0.036}^0$	M12-16