



FLANGE 13#

技术要求

- 未注倒角C0.5,锐边倒钝去毛刺;
Unquoted chamfer C0.5,break sharp edges
- 各表面不得有划伤,锈迹等缺陷;
All surfaces must be rust free and no scratch
- 未注尺寸公差按ISO 2768-MK标准;
dimensions without tolerance according to 2768-MK
- 节距偏差:任意相邻两齿 ± 0.03 ,90度圆弧内累计偏差在 ± 0.1 内;Pitch tolerance:within ± 0.03 for any neighboring two teeth within ± 0.1 for 90° arch
- 产品打字,装配紧定螺钉,Marking part No,Setscrews Installed

产品编号/Part No.	d	B	T	M
TRM4121_0	12 ^{+0.027} ₀	4 ± 0.015	13.8 ^{+0.1}	M4
TRM4127_0	15.88 ^{+0.027} ₀	4.76 ± 0.015	18.26 ^{+0.1}	10-24UNC

名称/Name: 同步轮				图号/Drawing No: TRM4121_0~4127_0		更新/Rev	
型号/Code: GT5M,Z24				材料/Material: LY12(2024-T6)		重量 比例	
共 页				第 页		3:1	
成都雷诺机械有限公司 Chengdu Leno Machinery Co.,Ltd Tel:+86-28-65998825;Fax:+86-28-84862968 sales@cdleno.com;www.cdleno.com				eno			